



● Viscosity Batter Mixer

- Stainless steel construction with US standard fasteners, bearings, sprockets, belting, and shafts.
- Stainless steel viscosity pump and motor with direct drive.
- 1/2 HP mixer.
- 2000 pounds per hour mixing capacity.
- Temperature monitoring in mix tank.
- 60,000 BTU rated cooling jacket.
- Cooling jacket to maintain acceptable temperatures for batter mix.
- Level control system to ensure proper amounts of batter at all times.
- Simple start-up sequence for more consistent and quicker start-ups.
- Shutdown feature that reduces batter waste.
- Easy access for maintenance
- Easy to clean, reducing food safety issues
- Sanitary stainless steel water piping

Pictured: AM 500 Viscosity Batter Mixer



www.abjequipfix.com

ABJ Warranty Policy

ABJ Equipfix will repair or replace any ABJ manufactured component that fails due to defect in material or workmanship within 12 months from shipment.

*All OEM parts covered by individual warranties.

THE MOST IMPORTANT PART OF A COATING SYSTEM IS THE ACCURACY OF THE BATTER MIXING. ABJ'S TOTAL VISCOSITY CONTROL MIXER ALLOWS PROCESSORS TO EXCEED THEIR QUALITY AS WELL AS YIELD EXPECTATIONS.